

Model	Boom Lift (mm / in.)	Boom Stroke (mm / in.)	Base Type	Boom Load (kg / lbs.)
M2020-S	2000 (78.75)	2000 (78.75)	Fixed "X" or Box Base	100 (220)
M2525-S	2500 (98.4)	2500 (98.4)	Fixed "X" or Box Base	100 (220)
M3030-S	3000 (118)	3000 (118)	Fixed "X" or Box Base	100 (220)
M3535-S	3500 (137.8)	3500 (137.8)	Fixed "X" or Box Base	100 (220)
M4040-S	4000 (157.5)	4000 (157.5)	Fixed "X" or Box Base	150 (330)
M5050-S	5000 (196.8)	5000 (196.8)	Fixed "X" or Box Base	150 (330)
<b>Standard Accessories</b>				
Fixed "X" or Box Base				
Manual Column Rotation				
Manual Column Clamping				
Proprietary Electrical & Control System				
Remote Pendant control with 6m cable				
Cable management system with column and boom mounted enclosed track				
<b>Optional Accessories</b>				
100 x 100 mm Manual Cross Slides				
200 x 200 mm Manual Cross Slides				
100x 100mm Power Cross Slides				
200 x 200 mm Power Cross Slides				
300 x 300 mm Power Cross Slides				
Manual Travel Car				
Power Travel Car (Variable Speed)				
Power Column Rotation and Clamping				
Mounting Platform for Welding Source				
Floor Mounted Flux Delivery & Recovery System (100 kg capacity)				
Lincoln DC600 / NA-3 Welding Package (inc. all brackets, cables and wires)				
Lincoln DC1000 / NA-3 Welding Package (inc. all brackets, cables and wires)				
Camera Monitoring System				
Seam Tracker System				
Welding Oscillator				